SAFETY DATA SHEET

Screen Print World Citrus Cleaner

According to the REACH etc. (Amendment etc.) (EU Exit) Regulations 2020 No. 1577, as amended.

SECTION 1: Identification of the	ne substance/mixture and of the company/undertaking
1.1. Product identifier	
Product name	Screen Print World Citrus Cleaner
Container size	500ml
EU REACH registration notes	All chemicals used in this product have been registered under REACH where required.
1.2. Relevant identified uses o	f the substance or mixture and uses advised against
Identified uses	Cleaning agent. Use only as directed.
1.3. Details of the supplier of the	he safety data sheet
Supplier	Screen Print World Limited Unit 8, Foley Business Park Kidderminster DY11 7PG Tel: (0)+44 1562 829 009 Email: info@screenprintworld.co.uk
1.4. Emorgonov tolonhono nur	
1.4. Emergency telephone nur Emergency telephone	Screen Print World Limited: (0)+44 1562 829 009 (Mon-Fri: 8:30- 5:00pm)
	9 IN AN EMERGENCY DIAL 999 / 112
number	For non-emergencies, call NHS 111 (24/7) or a doctor
SECTION 2: Hazards identification	ation
2.1. Classification of the subst	ance or mixture
Classification (SI 2019 No. 720	<u>))</u>
Physical hazards	Aerosol 1 - H222, H229
Health hazards	Skin Irrit. 2 - H315 Skin Sens. 1 - H317 Asp. Tox. 1 - H304
Environmental hazards	Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410
2.2. Label elements	
Hazard pictograms	
Signal word	Danger
Hazard statements	H222 Extremely flammable aerosol. H229 Pressurised container: may burst if heated. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements	 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P261 Avoid breathing spray. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. P501 Dispose of contents/ container in accordance with national regulations.
Contains	D-limonene
Supplementary precautionary statements	 P264 Wash contaminated skin thoroughly after handling. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P302+P352 IF ON SKIN: Wash with plenty of water. P321 Specific treatment (see medical advice on this label). P332+P313 If skin irritation occurs: Get medical advice/ attention. P333+P313 If skin irritation or rash occurs: Get medical advice/ attention. P362+P364 Take off contaminated clothing and wash it before reuse. P391 Collect spillage.

2.3. Other hazards

П

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients	
3.2. Mixtures	
D-limonene	60-100%
CAS number: 5989-27-5	EC number: 227-813-5
M factor (Acute) = 1	M factor (Chronic) = 1
Classification	
Flam. Liq. 3 - H226	
Skin Irrit. 2 - H315	
Skin Sens. 1 - H317	
Asp. Tox. 1 - H304	
Aquatic Acute 1 - H400	
Aquatic Chronic 1 - H410	
PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS 30-60	
(<0.1% 1,3 BUTADIENE)	
CAS number: 68476-85-7	EC number: 270-704-2
Classification	
Flam. Gas 1A - H220	
Press. Gas (Liq.) - H280	
The full text for all hazard sta	tements is displayed in Section 16.
Composition comments	Liquefied petroleum gases (CAS: 68476-85-7) contains less than 0.1% w/w 1,3-butadiene,

meaning that the full harmonised classification regarding Muta. 1B H340 and Carc. 1A H350 does not apply.

SECTION 4: First aid measures

4.1. Description of first aid measures General information Move affected person to fresh air at once. Inhalation Move affected person to fresh air at once. If breathing stops, provide artificial respiration. Keep affected person warm and at rest. Get medical attention immediately. Rinse mouth thoroughly with water. Do not induce vomiting. Get medical attention if any Ingestion discomfort continues. Skin contact Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues. Eye contact Rinse immediately with plenty of water. Continue to rinse for at least 15 minutes. Remove any contact lenses and open eyelids wide apart. Get medical attention promptly if symptoms occur after washing. 4.2. Most important symptoms and effects, both acute and delayed General information Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. Get medical attention promptly if symptoms occur after washing. Inhalation In case of overexposure, organic solvents may depress the central nervous system causing dizziness and intoxication, and at very high concentrations unconsciousness and death. Vapours may cause headache, fatigue, dizziness and nausea. There may be a feeling of tighness in the chest with shortness of breath. Ingestion May cause nausea, headache, dizziness and intoxication. Burning sensation in mouth. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation. Risk of lung aspiration due to low viscosity of product. Skin contact Skin irritation. Allergic rash. Eye contact Irritation of eyes and mucous membranes. 4.3. Indication of any immediate medical attention and special treatment needed Notes for the doctor Show this safety data sheet to the doctor in attendance. SECTION 5: Firefighting measures 5.1. Extinguishing media Suitable extinguishing media Use alcohol-resistant foam, carbon dioxide or dry powder to extinguish. Unsuitable extinguishing Do not use water jet as an extinguisher, as this will spread the fire. media 5.2. Special hazards arising from the substance or mixture Specific hazards May explode when heated or when exposed to flames or sparks. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. The product is extremely flammable. In use may form flammable/explosive vapourair mixture. Hazardous combustion Acrid smoke or fumes. Oxides of carbon. products 5.3. Advice for firefighters Use water spray to reduce vapours. Containers can burst violently or explode when heated, Protective actions during firefighting due to excessive pressure build-up. Cool containers exposed to flames with water until well after the fire is out. Bursting aerosol containers may be propelled from a fire at high speed. Special protective equipment Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective for firefighters clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures Personal precautions For personal protection, see Section 8. Ensure suitable respiratory protection is worn during removal of spillages in confined areas. Take precautionary measures against static discharges. No smoking, sparks, flames or other sources of ignition near spillage. Avoid inhalation of vapours and contact with skin and eyes. For non-emergency personnel Keep upwind to avoid inhalation of gases, vapours, fumes and smoke. For emergency responders For the greatest protection, clothing should include anti-static overalls, boots and gloves. Approach the spillage from upwind. 6.2. Environmental precautions **Environmental precautions** Do not discharge into drains or watercourses or onto the ground. 6.3. Methods and material for containment and cleaning up Methods for cleaning up Eliminate all sources of ignition. Provide adequate ventilation. Absorb in vermiculite, dry sand or earth and place into containers. Provide adequate ventilation. Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses. 6.4. Reference to other sections Reference to other sections Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see section 13. SECTION 7: Handling and storage 7.1. Precautions for safe handling Usage precautions Keep away from heat, sparks and open flame. Read and follow manufacturer's recommendations. Avoid inhalation of vapours and spray/mists. When sprayed on a naked flame or any incandescent material the aerosol vapours can be ignited. Do not spray on an open flame or other ignition source. Advice on general Wash after use and before eating, smoking and using the toilet. Use appropriate skin cream to occupational hygiene prevent drying of skin. Wash contaminated skin thoroughly after handling. 7.2. Conditions for safe storage, including any incompatibilities Storage precautions Keep away from heat, sparks and open flame. Store at temperatures not exceeding 50°C. Do not pierce or burn, even after use. Storage class **Extremely Flammable Aerosol** 7.3. Specific end use(s) Specific end use(s) The identified uses for this product are detailed in Section 1.2. Usage description Cleaning agent. SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

D-limonene

Short-term exposure limit (15-minute): WEL 150 ppm 10 minutes

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS (<0.1% 1,3 BUTADIENE)

Long-term exposure limit (8-hour TWA): WEL 1000 ppm 1750 mg/m³ Short-term exposure limit (15-minute): WEL 1250 ppm 2180 mg/m³

WEL = Workplace Exposure Limit.

	D-limonene (CAS: 5989-27-5)
DNEL	Consumer - Oral; Long term systemic effects: 4.44 mg/kg/day Consumer - Dermal; Long term systemic effects: 4.44 mg/kg/day Workers - Dermal; Long term systemic effects: 8.89 mg/kg/day Consumer - Inhalation; Long term systemic effects: 7.78 mg/m ³ Workers - Inhalation; Long term systemic effects: 31.1 mg/m ³
PNEC	 Fresh water; 0.054 mg/l Sediment (Freshwater); 1.3 mg/kg Intermittent release; 0.00577 mg/l Sediment (Marinewater); 0.13 mg/kg marine water; 0.0054 mg/l STP; 2.1 mg/l Soil; 0.261 mg/kg
Exposure controls	
ective equipment	

8.2. E

Prote





Appropriate engineering controls	Provide adequate ventilation.
Personal protection	Wear protective work clothing.
Eye/face protection	Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Tight-fitting safety glasses.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Frequent changes are recommended. The breakthrough time for any glove material may be different for different glove manufacturers. When used with mixtures, the protection time of gloves cannot be accurately estimated. It is recommended that gloves are made of the following material: Nitrile rubber.
Other skin and body protection	Provide eyewash station. Wear suitable gloves if prolonged or repeated skin contact is likely
Hygiene measures	Promptly remove any clothing that becomes wet or contaminated. Wash promptly if skin becomes contaminated. Do not eat, drink or smoke when using this product.
Respiratory protection	Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit. If ventilation is inadequate, suitable respiratory protection must be worn. Gas filter, type AX.
Thermal hazards	Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.
Environmental exposure controls	Residues and empty containers should be taken care of as hazardous waste according to local and national provisions.
SECTION 9: Physical and cl	hemical properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.	
Colour	Colourless to pale yellow.	
Odour	Citrus.	
Odour threshold	Not available.	
рН	Not available.	
Melting point	No information required.	
Initial boiling point and range	Liquefied petroleum gases: -40 to -2°C	
Flash point	No information required. A flash point method is not available but the major hazardous component, the liquefied petroleum gases, has a flash point of <-60°C with flammability limits of 10.9% vol. upper and 1.4% vol. lower.	
Evaporation rate	Not available.	
Evaporation factor	Not available.	
Flammability (solid, gas)	No information required.	
Upper/lower flammability or explosive limits	No information required.	
Vapour pressure	3 - 5 bar @ 20°C	
Vapour density	Not available.	
Relative density	Liquid base: 0.85 - 0.95 @ 25°C	
Solubility(ies)	Immiscible with water.	
Partition coefficient	Not available.	
Auto-ignition temperature	Liquefied petroleum gases: 365°C	
Viscosity	Liquid base: Kinematic viscosity ≤ 20.5 mm²/s.	
Explosive properties	In use may form flammable/explosive vapour-air mixture.	
Oxidising properties	Does not meet the criteria for classification as oxidising.	
9.2. Other information		
Particle size	No information required.	
Volatile organic compound	This product contains a maximum VOC content of 100 %.	
SECTION 10: Stability and rea	activity	
10.1. Reactivity		
Reactivity	Stable under recommended transport or storage conditions.	
10.2. Chemical stability		
Stability	Stable at normal ambient temperatures and when used as recommended.	
10.3. Possibility of hazardous	reactions	
Possibility of hazardous reactions	No known hazardous reactions if stored under normal conditions. Will not polymerise.	
10.4. Conditions to avoid		

Conditions to avoid	Avoid heat, flames and other sources of ignition. Avoid exposure to high temperatures or direct sunlight.
10.5. Incompatible materials	
Materials to avoid	Strong acids. Strong alkalis. Strong oxidising agents.
10.6. Hazardous decompositi	on products
Hazardous decomposition	Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and
products	other toxic gases or vapours.
SECTION 11: Toxicological in	nformation
11.1. Information on toxicolog	jical effects
Acute toxicity - oral	
Summary	Based on available data the classification criteria are not met.
Acute toxicity - dermal	Description and the data the start (for the science and much
Summary	Based on available data the classification criteria are not met.
Acute toxicity - inhalation	Deced on sucilable data the electrification with the one wat much
Summary	Based on available data the classification criteria are not met.
Skin corrosion/irritation	Causes skin irritation.
Summary	
Serious eye damage/irritation	
Summary	Based on available data the classification criteria are not met.
Respiratory sensitisation	Deced on sucilable data the electrification with the one wat much
Summary	Based on available data the classification criteria are not met.
Skin sensitisation	May source on ellerric skin resetion
Summary	May cause an allergic skin reaction.
Germ cell mutagenicity	Description and the data the start (for the science and much
Summary	Based on available data the classification criteria are not met.
Carcinogenicity	
Summary	Based on available data the classification criteria are not met.
Reproductive toxicity	
Summary	Based on available data the classification criteria are not met.
Specific target organ toxicity	
Summary	Based on available data the classification criteria are not met.
Specific target organ toxicity	
Summary	Based on available data the classification criteria are not met.
Aspiration hazard	
Summary	May be fatal if swallowed and enters airways.
Toxicological information on ingredients.	
	<u>D-limonene</u>

Acute toxicity - oral

Acute toxicity oral (LD50	4,400.0	
mg/kg)		
Species	Rat	
Notes (oral LD₅₀)	LD₅₀ >5000 mg/kg, Oral, Rat	
ATE oral (mg/kg)	4,400.0	
Acute toxicity - dermal		
Notes (dermal LD₅₀)	LD₅₀ >5000 mg/kg, Dermal, Rabbit	
Skin corrosion/irritation		
Skin corrosion/irritation	Irritating to skin.	
Serious eye damage/irritat	ion	
Serious eye damage/irritation	Based on available data the classification criteria are not met.	
Skin sensitisation		
Skin sensitisation	May cause an allergic skin reaction.	
Germ cell mutagenicity		
Genotoxicity - in vitro	Based on available data the classification criteria are not met.	
Genotoxicity - in vivo	Based on available data the classification criteria are not met.	
Carcinogenicity		
Carcinogenicity	Based on available data the classification criteria are not met.	
Reproductive toxicity		
Reproductive toxicity - fertility	Based on available data the classification criteria are not met.	
Specific target organ toxici	ty - single exposure	
STOT - single exposure	Based on available data the classification criteria are not met.	
Specific target organ toxici	ty - repeated exposure	
STOT - repeated exposure	Based on available data the classification criteria are not met.	
PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS (<0.1% 1,3 BUTADIENE)		
Toxicological effects	Information given is based on data of the components and of similar products.	
Acute toxicity - oral		
Notes (oral LD₅₀)	Not applicable.	
Acute toxicity - dermal		
Notes (dermal LD₅₀)	Not applicable.	
Acute toxicity - inhalation		
Notes (inhalation LC₅₀)	LC₅₀ >20 mg/l, Inhalation, Rat	
Skin corrosion/irritation		
Skin corrosion/irritation	Not irritating.	
Serious eye damage/irritat	ion	

	Serious eye damage/irritation	Not irritating.
	Respiratory sensitisation	
	Respiratory sensitisation	Not sensitising.
	Skin sensitisation	
	Skin sensitisation	Not sensitising.
	Germ cell mutagenicity	
	Genotoxicity - in vitro	This substance has no evidence of mutagenic properties.
	Carcinogenicity	
	Carcinogenicity	Carcinogenicity in humans is not expected.
	Reproductive toxicity	
	Reproductive toxicity - fertility	Based on available data the classification criteria are not met.
	Reproductive toxicity - development	Does not contain any substances known to be toxic to reproduction.
	Specific target organ toxici	ty - single exposure
	STOT - single exposure	A single exposure may cause the following adverse effects: Overexposure to organic solvents may depress the central nervous system, causing dizziness and intoxication and, at very high concentrations, unconsciousness and death.
	Specific target organ toxicity - repeated exposure STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.	
	STOT - repeated exposure	Not classified as a specific target organ toxicant after repeated exposure.
	STOT - repeated exposure Aspiration hazard	Not classified as a specific target organ toxicant after repeated exposure.
		 Not classified as a specific target organ toxicant after repeated exposure. Based on available data the classification criteria are not met.
	Aspiration hazard	
	Aspiration hazard Aspiration hazard	Based on available data the classification criteria are not met.
	Aspiration hazard Aspiration hazard Inhalation	Based on available data the classification criteria are not met. May cause respiratory system irritation. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in
SECTION 1	Aspiration hazard Aspiration hazard Inhalation Skin contact	Based on available data the classification criteria are not met. May cause respiratory system irritation. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.
SECTION 1 Ecotoxicity	Aspiration hazard Aspiration hazard Inhalation Skin contact Route of exposure 2: Ecological information Avoid th	Based on available data the classification criteria are not met. May cause respiratory system irritation. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin.
Ecotoxicity	Aspiration hazard Aspiration hazard Inhalation Skin contact Route of exposure 2: Ecological information Avoid th	Based on available data the classification criteria are not met. May cause respiratory system irritation. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin. Inhalation Skin and/or eye contact
Ecotoxicity	Aspiration hazard Aspiration hazard Inhalation Skin contact Route of exposure 2: Ecological information Avoid th with lone	Based on available data the classification criteria are not met. May cause respiratory system irritation. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin. Inhalation Skin and/or eye contact
Ecotoxicity	Aspiration hazard Aspiration hazard Inhalation Skin contact Route of exposure 2: Ecological information Avoid th with long	Based on available data the classification criteria are not met. May cause respiratory system irritation. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin. Inhalation Skin and/or eye contact e spillage or runoff entering drains, sewers or watercourses. Very toxic to aquatic life g lasting effects. <u>D-limonene</u>
Ecotoxicity	Aspiration hazard Aspiration hazard Inhalation Skin contact Route of exposure 2: Ecological information Avoid th with lone	Based on available data the classification criteria are not met. May cause respiratory system irritation. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin. Inhalation Skin and/or eye contact e spillage or runoff entering drains, sewers or watercourses. Very toxic to aquatic life g lasting effects.
Ecotoxicity	Aspiration hazard Aspiration hazard Inhalation Skin contact Route of exposure 2: Ecological information Avoid th with long	Based on available data the classification criteria are not met. May cause respiratory system irritation. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin. Inhalation Skin and/or eye contact e spillage or runoff entering drains, sewers or watercourses. Very toxic to aquatic life g lasting effects. <u>D-limonene</u>
Ecotoxicity	Aspiration hazard Aspiration hazard Inhalation Skin contact Route of exposure 2: Ecological information Avoid th with long	Based on available data the classification criteria are not met. May cause respiratory system irritation. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin. Inhalation Skin and/or eye contact e spillage or runoff entering drains, sewers or watercourses. Very toxic to aquatic life g lasting effects. <u>D-limonene</u> Very toxic to aquatic life with long lasting effects.
Ecotoxicity	Aspiration hazard Aspiration hazard Inhalation Skin contact Route of exposure 2: Ecological information Avoid th with long formation on ingredients. Ecotoxicity Ecotoxicity	Based on available data the classification criteria are not met. May cause respiratory system irritation. Spray will evaporate and cool rapidly and may cause frostbite or cold burns if in contact with skin. Inhalation Skin and/or eye contact e spillage or runoff entering drains, sewers or watercourses. Very toxic to aquatic life g lasting effects. <u>D-limonene</u> Very toxic to aquatic life with long lasting effects. <u>MGASES, LIQUEFIED; PETROLEUM GAS (<0.1% 1,3 BUTADIENE)</u>

Toxicity

Contains a substance which is very toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment ..

Ecological information on ingredients.

D-limonene

Acute aquatic toxicity		
LE(C)₅₀	0.1 < L(E)C50 ≤ 1	
M factor (Acute)	1	
Acute toxicity - fish	LC₅₀, 96 hours: 0.71 mg/l, Pimephales promelas (Fat-head Minnow)	
Acute toxicity - aquatic invertebrates	EC₅₀, : 0.4 mg/l, Daphnia magna	
Acute toxicity - aquatic plants	IC₅₀, : 4 mg/l, Algae	
Chronic aquatic toxicity		
M factor (Chronic)	1	
PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS (<0.1% 1,3 BUTADIENE)		
Toxicity	Not regarded as dangerous for the environment. The product is not believed to present a hazard due to its physical nature. Highly volatile.	
12.2. Persistence and degradability		
Persistence and degradability No data available.		
Ecological information on ingredients.		
	<u>D-limonene</u>	
Persistence and degradability	The product is biodegradable.	

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS (<0.1% 1,3 BUTADIENE)

Persistence and

The product is readily biodegradable.

degradability

12.3. Bioaccumulative potential

Bioaccumulative potential No data available on bioaccumulation.

Partition coefficient Not available.

Ecological information on ingredients.

D-limonene

Bioaccumulative potential BCF: 32-156(I),

PETROLEUM GASES, LIQUEFIED; PETROLEUM GAS (<0.1% 1,3 BUTADIENE)

Bioaccumulative potential Bioaccumulation is unlikely.

12.4. Mobility in soil

Mobility	The product contains organic solvents which will evaporate easily from all surfaces. The product is miscible with water and may spread in water systems.	
Ecological information on ingre-	dients.	
	D-limonene	
Mobility	No data available.	
PE	TROLEUM GASES, LIQUEFIED; PETROLEUM GAS (<0.1% 1,3 BUTADIENE)	
Mobility	The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.	
12.5. Results of PBT and vPvB	assessment	
Results of PBT and vPvB assessment	This product does not contain any substances classified as PBT or vPvB.	
Ecological information on ingre	dients.	
	D-limonene	
Results of PBT an assessment	nd vPvB This substance is not classified as PBT or vPvB according to current UK criteria.	
PE	TROLEUM GASES, LIQUEFIED; PETROLEUM GAS (<0.1% 1,3 BUTADIENE)	
Results of PBT an assessment	ud vPvB This product does not contain any substances classified as PBT or vPvB.	
12.6. Other adverse effects		
Other adverse effects	None known.	
SECTION 13: Disposal conside	arations	
13.1. Waste treatment methods	3	
General information	Do not puncture or incinerate, even when empty. Ensure containers are empty before discarding (explosion risk). Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.	
Disposal methods	Containers should be thoroughly emptied before disposal because of the risk of an explosion. Do not puncture or incinerate, even when empty. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.	
Waste class	Empty Aerosol: 15 01 10 (Containing hazardous residues), Empty Aerosol: 15 01 04 (No hazardous residues). Full or Partially Empty Aerosol: 16 05 04,	
SECTION 14: Transport inform	ation	
14.1. UN number		
UN No. (ADR/RID)	1950	
UN No. (IMDG)	1950	
UN No. (ICAO)	1950	
UN No. (ADN)	1950	
14.2. UN proper shipping name)	

Proper shipping name (ADR/RID)	AEROSOLS	
Proper shipping name (IMDG)	AEROSOLS, MARINE POLLUTANT (D-LIMONENE)	
Proper shipping name (ICAO)	AEROSOLS	
Proper shipping name (ADN)	AEROSOLS	
14.3. Transport hazard class(es)		
ADR/RID class	2.1	
ADR/RID classification code	5F	
ADR/RID label	2.1	
IMDG class	2.1	
ICAO class/division	2.1	
ADN class	2.1	

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

IMDG Code segregation group	SG69, SW1, SW22
EmS	F-D, S-U
ADR transport category	2
Tunnel restriction code	(D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	Control of Substances Hazardous to Health Regulations 2002 (as amended). The Aerosol Dispensers Regulations 2009 (SI 2009 No. 2824).
Authorisations (SI 2020 No. 1577 Annex XIV)	No specific authorisations are known for this product.

Restrictions (SI 2020 No.No specific restrictions on use are known for this product.1577 Annex XVII)

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

Classification procedures according to SI 2019 No. 720	Aerosol 1 - H222, H229: Weight of evidence. Asp. Tox. 1 - H304: On basis of test data., Kinematic viscosity ≤ 20.5 mm²/s. Skin Irrit. 2 - H315, Skin Sens. 1 - H317, Aquatic Acute 1 - H400, Aquatic Chronic 1 - H410: Calculation method.
Issued by	Technical Department
Revision date	20/05/2022
Revision	5
Supersedes date	09/02/2021
SDS number	24131
Hazard statements in full	 H220 Extremely flammable gas. H222 Extremely flammable aerosol. H226 Flammable liquid and vapour. H229 Pressurised container: may burst if heated. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.